

PRODUCT DATA SHEET

FlexiTog[®]



COFRA BRAGI FREEZER BOOT FB72

Ref: FB72

Variants: 6 (39) , 6.5 (40) , 7 (41) , 8 (42) , 9 (43) , 10 (44) , 10.5 (45) , 11 (46) , 12 (47)

Area of use: Cold Store / Freezer -5 to -50°C , Chiller+5 to -5°C

Job role: Driver , Picker

Gender: Unisex



Certification 1: EN ISO 20345: 2011
S3 CI HRO SRC

Certification Valid Until: 12/03/2023

Updated On: 20/06/2025

Email: sales@flexitog.com
Phone: +31 174 705 840
Website: <https://www.flexitog.eu>

FlexiTog UK
FlexiTog UK Ltd
The Granary Business Park
School Road, Neatishead
Norfolk
NR12 8BU
United Kingdom

FlexiTog EU
Graandijk 1
5704 RB Helmond
Netherlands

PRODUCT DATA SHEET

The logo for FlexiTog, featuring the brand name in a white, bold, sans-serif font with a registered trademark symbol, set against a solid red rectangular background.

Weight	1.0 kg
Product Material	Leather upper/rubber sole
Packaging	Shoe Box
Storage Instructions	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
Commodity Code	64039193 Footwear non-identifiable as men's or women's footwear, with outer soles of rubber, plastics or composition leather, with uppers of leather, covering the ankle, with in-soles of a length >= 24 cm (excl. 6403.1-00 to 6403.40.00)
Country of Origin	Italy

Email: sales@flexitog.com
Phone: +31 174 705 840
Website: <https://www.flexitog.eu>

FlexiTog UK
FlexiTog UK Ltd
The Granary Business Park
School Road, Neatishead
Norfolk
NR12 8BU
United Kingdom

FlexiTog EU
Graandijk 1
5704 RB Helmond
Netherlands

PRODUCT DATA SHEET



OVERVIEW

- EVA and Nitrile antistatic sole
- Thinsulate insulation
- Composite toe cap resistant to 200 J
- Composite midsole
- Side zip
- Cold Protection (CI) certified

Email: sales@flexitog.com
Phone: +31 174 705 840
Website: <https://www.flexitog.eu>

FlexiTog UK
FlexiTog UK Ltd
The Granary Business Park
School Road, Neatishead
Norfolk
NR12 8BU
United Kingdom

FlexiTog EU
Graandijk 1
5704 RB Helmond
Netherlands