

PRODUCT DATA SHEET

FlexiTog®



Safety Shoe S3 Src Alabama

An extremely comfortable and lightweight safety shoe for chilled and ambient areas.

Ref: [FT]FA306

Variants: 4 (37) , 5 (38) , 6 (39) , 6.5 (40) , 7 (41) , 8 (42) , 9 (43) , 10 (44) , 10.5 (45) , 11 (46) , 12 (47) , 13 (48)

Area of use: Chiller +5 to -5°C , Cold Weather / Ambient

Job role: Driver , Picker , Manager

Gender: Male , Unisex



Certification 1: EN ISO 20345:2011
S3 SRC

Certification Valid Until: 01/11/2025

Updated On: 20/06/2025

PRODUCT DATA SHEET

The logo for FlexiTog, featuring the brand name in a white, bold, sans-serif font on a red rectangular background.

Weight	1.29 kg
Product Material	Micro-nubuck with anti-abrasion microfibre upper/PU sole
Packaging	Cardboard Box
Storage Instructions	Store in a dry place protect against high temperatures and uv rays exposure, once removed from the original packaging, it can be stored in a cupboard.
CAT	II
DoC	The PPE detailed herein meets the criteria of Article 19(b) Risk Category II: internal production control (module B) set out in Annex V, followed by conformity of type based on internal production control (module C) set out in Annex VI, in accordance with PPE Regulation (EU) 2016/425, (UK only) as brought into UK law and amended Essential Health and Safety Requirements.
Commodity Code	64034000 Footwear, incorporating a protective metal toecap, with outer soles of rubber, plastics, leather or composition leather and uppers of leather (excl. sports footwear and orthopaedic footwear)
Country of Origin	Italy

Email: sales@flexitog.com
Phone: +31 174 705 840
Website: <https://www.flexitog.eu>

FlexiTog UK
FlexiTog UK Ltd
The Granary Business Park
School Road, Neatishead
Norfolk
NR12 8BU
United Kingdom

FlexiTog EU
Graandijk 1
5704 RB Helmond
Netherlands

Fortdr
Duisbu
57234
Germa

PRODUCT DATA SHEET



OVERVIEW

- Metal free - excellent for operatives working near metal detectors.
- micro-nubuck upper.
- Breathable, abrasion resistant lining.
- Pierce resistance.
- 200J non-metallic toecap.
- PU anti-slip SRC rated sole.